HP Color LaserJet Professional CP5220 Printer series





Cover all your colour business printing needs from postcards to oversize documents, with this versatile and affordable A3 desktop printer. Get superior print quality with HP ColorSphere toner, fast speeds and ease of use, with unrivalled reliability.

For small workteams from 3-15 users in unmanaged environments in small and medium sized businesses, who need a versatile printer for all their printing needs, from spreadsheets, marketing materials and client presentations to oversize documents.

Handle all your business printing with this affordable, versatile A3 colour printer.

Print everyday business documents as well as wide-format projects, and save money by printing colour marketing materials in house. Enjoy exceptional versatility: print from postcard-size up to poster-size and on a variety of paper types including plain, premium and glossy and weights up to 220 gsm. Handle big jobs easily with an expandable input capacity: from 350 sheets standard with 100-sheet multipurpose tray and 250-sheet tray, up to a maximum of 850 sheets with an optional 500-sheet tray.

Achieve consistently high-quality output with HP ColorSphere toner on a range of business documents.

Get sharp, black text and vibrant colour: Original HP cartridges with HP ColorSphere toner deliver consistent, professional quality results on a range of documents. Achieve superior print quality at high speeds of up to 20 ppm black and colour A4. Start fast and finish sooner with Instant-on Technology which provides a first page out in less than 18 seconds from low-power mode. See amazing results with HP ImageREt 3600, image resolution technology that creates smooth colours and sharp images.

Simple to use, share, and maintain with an intuitive control panel and easily replaced supplies.

Easy to use – an intuitive control panel shows clear device status communications. Connect your printer directly to a computer with the High-speed USB 2.0 port and cable. Easily connect to a network and share resources among up to 15 users ¹ using built-in Fast Ethernet 10/100 Base-T networking. Minimise printer interaction with easy-to-replace all-in-one print cartridges and convenient front-door supplies access. Time-saving tools include HP SureSupply² and HP Easy Printer Care Software.



 2 HP SureSupply programme features and availability may vary by country For more information, visit www.hp.com/learn/suresupply



HP Color LaserJet Professional CP5225 Printer



HP Color LaserJet Professional CP5225n Printer



HP Color LaserJet Professional CP5225dn Printer

Product walkground

HP Color LaserJet Professional CP5225dn Printer shown

- 1. 250-sheet top output bin
- 2. One-door access to the easy to-install print cartridges
- 3. 250-sheet input tray 2 with close-assist
- 4. Intuitive control panel with two-line LCD display
- 5. 100-sheet multipurpose tray with long paper extension handles a variety of special papers
- 6. Illuminated front-access On/Off switch
- 7. 192 MB memory expandable to 448 MB, and a 540 MHz processor
- 8. Built-in Fast Ethernet 10/100 Base-T networking with IPv4/IPv6 allows up to 15 users to easily share the
- 9. Hi-Speed USB 2.0 port for direct connection to printer
- 10. In-line (one-pass) print engine ensures reliable, accurate print quality
- 11. Built-in automatic two-sided printing



Series at a glance



HP Color LaserJet Professional CP5225 Printer

- Print speed of up to 20 ppm black and colour
- ImageREt 3600
- 600 x 600 dpi effective output quality
- 192 MB
- expandable to 448 MB via one open DDR2 DIMM slot
- 540 MHz processor
- standard input capacity of 350-sheets with one 100-sheet multi-purpose tray 1 and 250-sheet input tray 2 plus optional 500-sheet tray 3



HP Color LaserJet Professional CP5225n Printer

Base-T networking



HP Color LaserJet Professional CP5225dn Printer

As base model plus built-in Fast Ethernet 10/100 • As base model plus automatic two-sided printing and built-in Fast Ethernet 10/100 Base-T networking

Recommended accessories



Q6264A

J8021A HP Jetdirect ew2500 802.11b/g Wireless Print

CE860A
HP Color LaserJet 500-sheet
Paper Tray
Enhance productivity with a
simple-to-install paper tray
that allows you to print more
pages without reloading
paper and keep two
different types of paper
loaded.

CB421A
HP 64 MB DDR2 144-pin
DIMM
Improve printing
performance of complex
documents by enhancing
data flow with HP memory
upgrades.

CB422A
HP 128 MB DDR2 144-pin
DIMM
Improve printing
performance of complex
documents by enhancing
data flow with HP memory
upgrades.

CB423A
HP 256 MB DDR2 144-pin
DIMM
Improve printing
performance of complex
documents by enhancing
data flow with HP memory
upgrades.

HP Hi-Speed USB Cable (6 ft./1.8 m)
The HP Hi-Speed USB Cable easily connects your printer with a PC or Mac. It reliably delivers speeds of up to 480 Mbps and is perfect for connecting your computer to the printer on your desk.

Ordering information



HP Color LaserJet Professional CP5225 Printer (CE710A)
Printer, power cord, Getting Started Guide, CD with software
and documentation, preinstalled black, cyan, magenta, and
yellow HP Color LaserJet print cartridges with HP ColorSphere
toner, 100-sheet multipurpose tray, 250-sheet input tray



HP Color LaserJet Professional CP5225n Printer (CE711A)
Printer, power cord, Getting Started Guide, CD with software
and documentation, built-in Fast Ethernet 10/100 Base-T
networking, preinstalled black, cyan, magenta and yellow HP
Color LaserJet print cartridges with HP ColorSphere toner,
100-sheet multipurpose tray, 250-sheet input tray



HP Color LaserJet Professional CP5225dn Printer (CE712A)
Printer, power cord, Getting Started Guide, CD with software
and documentation, built-in Fast Ethernet 10/100 Base-T
networking, built-in automatic two-sided printing, preinstalled
black, cyan, magenta and yellow HP Color LaserJet print
cartridges with HP ColorSphere toner, 100-sheet multipurpose
tray, 250-sheet input tray

Accessories, Supplies and Support

Accessories				
CE860A	HP Color LaserJet 500-sheet Paper Tray			
CB421A	HP 64 MB DDR2 144-pin DIMM			
CB422A	HP 128 MB DDR2 144-pin DIMM			
CB423A	HP 256 MB DDR2 144-pin DIMM			
Supplies				
CE740A	HP Color LaserJet CE740A Black Print Cartridge Average cartridge yields 7000 standard pages. Declared yield value in accordance with ISO/IEC 19798*			
CE741A	HP Color LaserJet CE741A Cyan Print Cartridge Average cartridge yields 7300 standard pages. Declared yield value in accordance with ISO/IEC 19798*			
CE742A	HP Color LaserJet CE742A Yellow Print Cartridge Average cartridge yields 7300 standard pages. Declared yield value in accordance with ISO/IEC 19798*			
CE743A	HP Color LaserJet CE743A Magenta Print Cartridge Average cartridge yields 7300 standard pages. Declared yield value in accordance with ISO/IEC 19798*			

 Connectivity

 C6518A
 HP USB Cable, 2m

 Q6264A
 HP Hi-Speed USB Cable (6 ft./1.8 m)

 J8021A
 HP Jetdirect ew2500 802.11b/g Wireless Print Server

Service & support

UT431E HP Care Pack, Next Business Day On-site Color LaserJet CP5225 Hardware Support, 3 years UQ497E HP Care Pack, 4-Hour, 13x5 Same Business Day On-site Color LaserJet CP5225 Hardware Support, 3 years

UT430E HP Care Pack, Next Business Day On-site Color LaserJet CP5225 Hardware Support, 4 years

UQ502E HP Care Pack, Next Business Day On-site Color LaserJet CP5225 Hardware Support, 5 years

UQ498PE HP Care Pack, Post Warranty Service, Next Business Day On-site Color LaserJet CP5225 Hardware Support, 1 year UQ492PE HP Care Pack, Post Warranty Service, 4-Hour, 13x5 Same Business Day On-site Color LaserJet CP5225 Hardware

Support, 1 year '
For a complete list of supplies, accessories and services, please refer tohttp://www.hp.com



Technical specifications

	Laser						
Print speed	First page out Black: < 16 sec (from "ready"), Colour: < 17 sec (from "ready") A4 Black: Up to 20 ppm , Colour: Up to 20 ppm						
	Exact speed varies depending on the system configuration, software application, driver and document complexity.						
Processor		540 MHz, Motorola Coldfire® V5x					
Memory		DR2 DIMM , Expandable to 448 MB through one D	DDR2 DIMM slot				
Print resolution		Black: Up to 600 x 600 dpi					
Tim resolution	Colour: Up to 600 x 600 dpi						
Print quality	HP ImageREt 3600						
Printer languages		5c, HP Postscript level 3 emulation					
Typefaces/fonts	84 scalable TrueTyp						
Duty cycle (monthly, A4)	Up to 75000 page						
Recommended Monthly Page Volume	1 1 3	up to 75000 pages 1500 to 5000					
		100 : 1: 100 1 :: 100					
Print margins	top: 4.23 mm, left: 4.23 mm, right: 4.23 mm, bottom: 4.23 mm						
Media handling	Input Tray 1	Capacity sheets: 100, envelopes: 20	Weight 60 to 220 g/m ²	Size A3, A4, A5, A6, RA3, SRA3, B4, B5, 10 x 15 cm, envelopes (DL, C5, B5), 76 x 127 to 320 x 457 mm			
	Tray 2	sheets: 250	Up to 120 g/m² plain papers, up to 160 g/m² coated papers	A3, A4, A5, B4, B5, 148 x 182 to 297 x 432 mm			
	Tray 3	sheets: 500	Up to 120 g/m² plain papers, up to 160 g/m² coated papers	A3, A4, B4, B5, 148 x 210 to 297 x 432 mm			
	Duplex printing:	CP5225: Manual (driver support provided); CP5225n: Manual (driver support provided); CP5225dn: Automatic (standard)	Up to 120 g/m² non-coated papers, up to 160 g/m² coated papers)	A3; A4; A5; SRA3; B4; B5			
	Output:	Sheets: Up to 250. Envelopes: Up to 15					
Media types	Paper (bond, broch	ure, coloured, glossy, letterhead, photo, plain, pre	printed, prepunched, recycled, rough), cardstock, gl	ossy film, transparencies, labels, envelopes			
Interface and connectivity			st Ethernet 10/100Base-TX; CP5225dn: Hi-Speed U				
Network Capabilities		DBase-TX networking	, , , , , , , , , , , , , , , , , , , ,	,			
Operating systems compatibility		Microsoft® Windows® 2000, XP Home, XP Professional, Server 2003, XP Media Center, XP Professional x64; Windows Vista®; Windows® 7 (HP UPD only); Mac OS X					
	v10.3, v10.4 or higher; Linux (see http://www.hplip.net) Optional: Latest printer driver information available at http://www.hp.com/support						
Network operating systems compatibility	Microsoft® Window	Microsoft® Windows® 2000, XP Home, XP Professional, Server 2003, XP Media Center, XP Professional x64; Windows Vista®; Windows® 7 (HP UPD only); Mac OS X v10.3, v10.4 or higher; Linux (see http://www.hplip.net)					
	Microsoft® Windows® 2000, Server 2003: any Pentium® II processor or higher, 64 MB RAM, 250 MB hard disk space, USB or Ethernet port; (print driver only); Microsoft® Windows® XP-32 Home, XP-32 Professional: any Pentium® II processor (Pentium® III or higher recommended), 128 MB RAM, 250 MB hard disk space, USB port; (full install); Microsoft® Windows® XP-34: any Pentium® II processor (Pentium® III or higher recommended), 128 MB RAM, 250 MB hard disk space, USB or Etherne port; (print driver only); Windows Vista®-32 Home, -32 Professional: 1 GHz processor, 512 MB RAM, 250 MB hard disk space, USB or Ethernet port; (full install); Windows Vista®-64: 1 GHz processor, 512 MB RAM, 250 MB hard disk space, USB port; (full install); SVGA 800 x 600 with 16-bit colour display, CD-ROM drive, Internet Explorer 5.5 or higher, Mac OS X v10.3 or higher; PowerPC G3, G4, G5, or Intel® Core processor; 150 MB available hard disk space; CD-ROM drive; USB or Ethernet port						
Minimum system requirements	port; (full install); N port; (print driver o Vista®-64: 1 GHz	ticrosoft® Windows® XP-x64: any Pentium® II pro- nly); Windows Vista®-32 Home, -32 Professional: processor, 512 MB RAM, 250 MB hard disk space	1 GHz processor, 512 MB RAM, 250 MB hard disle, USB port; (full install); SVGA 800 \times 600 with 16-	c space, USB or Ethernet port; (full install); Windows bit colour display, CD-ROM drive, Internet Explorer			
Minimum system requirements Software	port; (full install); N port; (print driver o Vista®-64: 1 GHz 5.5 or higher, Mac	ticrosoft® Windows® XP-x64: any Pentium® II pro- nly); Windows Vista®-32 Home, -32 Professional: processor, 512 MB RAM, 250 MB hard disk space OS X v10.3 or higher; PowerPC G3, G4, G5, or	1 GHz processor, 512 MB RAM, 250 MB hard disle, USB port; (full install); SVGA 800 x 600 with 16-Intel® Core processor; 150 MB available hard disk	c space, USB or Ethernet port; (full install); Windows bit colour display, CD-ROM drive, Internet Explorer			
Software	port; (full install); N port; (print driver o Vista®-64: 1 GHz 5.5 or higher, Mac Print driver (HP PCL	ticrosoft® Windows® XP-x64: any Pentium® II pro- nly); Windows Vista®-32 Home, -32 Professional: processor, 512 MB RAM, 250 MB hard disk space OS X v10.3 or higher; PowerPC G3, G4, G5, or .6), Toolbox FX configuration utility, SNP alerts and	1 GHz processor, 512 MB RAM, 250 MB hard disle, USB port; (full install); SVGA 800 x 600 with 16-Intel® Core processor; 150 MB available hard disk d installation software on CD-ROM	c space, USB or Ethernet port; (full install); Windows bit colour display, CD-ROM drive, Internet Explorer space; CD-ROM drive; USB or Ethernet port			
Control panel	port; (full install); N port; (print driver o Vista®-64: 1 GHz 5.5 or higher, Mac Print driver (HP PCL 2-line, 16-character	ticrosoft® Windows® XP-x64: any Pentium® II pro- nly); Windows Vista®-32 Home, -32 Professional: processor, 512 MB RAM, 250 MB hard disk space OS X v10.3 or higher; PowerPC G3, G4, G5, or .6), Toolbox FX configuration utility, SNP alerts and r backlit front panel display, 5 buttons (Cancel job,	1 GHz processor, 512 MB RAM, 250 MB hard disle, USB port; (full install); SVGA 800 x 600 with 16-Intel® Core processor; 150 MB available hard disk	c space, USB or Ethernet port; (full install); Windows bit colour display, CD-ROM drive, Internet Explorer space; CD-ROM drive; USB or Ethernet port			
Software Control panel Printer management	port; (full install); N port; (print driver o Vista®-64: 1 GHz 5.5 or higher, Mac Print driver (HP PCL 2-line, 16-character SNP (default install)	ticrosoft® Windows® XP-x64: any Pentium® II pro- nly); Windows Vista®-32 Home, -32 Professional: processor, 512 MB RAM, 250 MB hard disk space. OS X v10.3 or higher; PowerPC G3, G4, G5, or . 6), Toolbox FX configuration utility, SNP alerts and r backlit front panel display, 5 buttons (Cancel job,), Toolbox FX (additional software install)	1 GHz processor, 512 MB RAM, 250 MB hard disle, USB port; (full install); SVGA 800 x 600 with 16-Intel® Core processor; 150 MB available hard disk distallation software on CD-ROM, Left arrow, Right arrow, Select, Back), 2 LEDs (Atter	c space, USB or Ethernet port; (full install); Windows bit colour display, CD-ROM drive, Internet Explorer space; CD-ROM drive; USB or Ethernet port			
Software Control panel	port; (full install); N port; (print driver o Vista®-64: 1 GHz 5.5 or higher, Mac Print driver (HP PCL 2-line, 16-character SNP (default install Memory upgradeal Requirements: Inpu	ticrosoft® Windows® XPx64: any Pentium® II pronly; Windows Vista®-32 Home, -32 Professional: processor, 512 MB RAM, 250 MB hard disk space OS X v10.3 or higher; PowerPC G3, G4, G5, or 6), Toolbox FX configuration utility, SNP alerts and backlit front panel display, 5 buttons (Cancel job, 7, Toolbox FX (additional software install) ble to 448 MB, optional 500 sheet tray, only one of voltage 115 to 127 VAC (+/-10%), 60 Hz (+/-10%).	1 GHz processor, 512 MB RAM, 250 MB hard disle, USB port; (full install); SVGA 800 x 600 with 16-Intel® Core processor; 150 MB available hard disk distallation software on CD-ROM, Left arrow, Right arrow, Select, Back), 2 LEDs (Atteradditional tray may be added 2 Hz), 12 A; 220 to 240 VAC (+/- 10%), 50 Hz (+	c space, USB or Ethernet port; (full install); Windows bit colour display, CD-ROM drive, Internet Explorer space; CD-ROM drive; USB or Ethernet port			
Software Control panel Printer management Upgradability	port; (full install); N port; (print driver o Vista®-64: 1 GHz 5.5 or higher, Mac Print driver (HP PCL 2-line, 16-character SNP (default install Memory upgradeal Requirements: Input watts (standby), 4. Out of package: C	ticrosoft® Windows® XP-x64: any Pentium® II pronhly; Windows Vista®-32 Home, -32 Professional: processor, 512 MB RAM, 250 MB hard disk space. OS X v10.3 or higher; PowerPC G3, G4, G5, or. 6), Toolbox FX configuration utility, SNP alerts and broadling from the panel display, 5 buttons (Cancel job, 1), Toolbox FX (additional software install) ble to 448 MB, optional 500 sheet tray, only one of the voltage 115 to 127 VAC (+/- 10%), 60 Hz (+/- 4 watts (powersave), 0.5 watts (off); Typical Electric P5225: 545 x 599 x 338 mm; CP5225n: 545 x 5	1 GHz processor, 512 MB RAM, 250 MB hard disle, USB port; (full install); SVGA 800 x 600 with 16-Intel® Core processor; 150 MB available hard disk d installation software on CD-ROM, Left arrow, Right arrow, Select, Back), 2 LEDs (Atteradditional tray may be added 2 Hz), 12 A; 220 to 240 VAC (+/- 10%), 50 Hz (+city Consumption (TEC): 1.787 kWh/Week 99 x 338 mm; CP5225dn: 545 x 599 x 338 mm	c space, USB or Ethernet port; (full install); Windows bit colour display, CD-ROM drive, Internet Explorer space; CD-ROM drive; USB or Ethernet port			
Software Control panel Printer management Upgradability Power	port; (full install); N port; (print driver o Vista®-64: 1 GHz 5.5 or higher, Mac Print driver (HP PCL 2-line, 16-character SNP (default install Memory upgradeal Requirements: Input watts (standby), 4. Out of package: C	ticrosoft® Windows® XP-x64: any Pentium® II pronhly; Windows Vista®-32 Home, -32 Professional: processor, 512 MB RAM, 250 MB hard disk space. OS X v10.3 or higher; PowerPC G3, G4, G5, or. 6), Toolbox FX configuration utility, SNP alerts and backlit front panel display, 5 buttons (Cancel job,), Toolbox FX (additional software install) ble to 448 MB, optional 500 sheet tray, only one of voltage 115 to 127 VAC (+/- 10%), 60 Hz (+/- 4 watts (powersave), 0.5 watts (off); Typical Electric PS225: 545 x 599 x 338 mm; CF5225n: 545 x 55 x 56; 718 x 702 x 478 mm; CF5225n: 718 x 702 x 478 mm; CF5225n: 718 x 702 x 478 mm;	1 GHz processor, 512 MB RAM, 250 MB hard disle, USB port; (full install); SVGA 800 x 600 with 16-Intel® Core processor; 150 MB available hard disk d installation software on CD-ROM, Left arrow, Right arrow, Select, Back), 2 LEDs (Atteradditional tray may be added 2 Hz), 12 A; 220 to 240 VAC (+/- 10%), 50 Hz (+city Consumption (TEC): 1.787 kWh/Week 99 x 338 mm; CP5225dn: 545 x 599 x 338 mm	c space, USB or Ethernet port; (full install); Windows bit colour display, CD-ROM drive, Internet Explorer space; CD-ROM drive; USB or Ethernet port			
Software Control panel Printer management Upgradability Power Dimensions (w x d x h)	port; (full install); N port; (print driver o Vista®-64: 1 GHz 5.5 or higher, Mac Print driver (HP PCL 2-line, 16-character SNP (default install Memory upgradeal Requirements: Input watts (standby), 4.0 Out of package: CP5225 Out of package: CP5225 Out of package: Al Packaged: 43 kg	ticrosoft® Windows® XPx64: any Pentium® II pronly); Windows Vista®-32 Home, -32 Professional: processor, 512 MB RAM, 250 MB hard disk space. OS X v10.3 or higher; PowerPC G3, G4, G5, or .6), Toolbox FX configuration utility, SNP alerts and backlit front panel display, 5 buttons (Cancel job,), Toolbox FX (additional software install) ble to 448 MB, optional 500 sheet tray, only one of tooltage 115 to 127 VAC (+/- 10%), 60 Hz (+/- 24 watts (powersave), 0.5 watts (off); Typical Electric P5225: 545 x 599 x 338 mm; CP5225n: 545 x 50.9 kg	1 GHz processor, 512 MB RAM, 250 MB hard disle, USB port; (full install); SVGA 800 x 600 with 16-Intel® Core processor; 150 MB available hard disk distallation software on CD-ROM, Left arrow, Right arrow, Select, Back), 2 LEDs (Atteractional tray may be added 2 Hz), 12 A; 220 to 240 VAC (+/- 10%), 50 Hz (+city Consumption (TEC): 1.787 kWh/Week 99 x 338 mm; CP5225dn: 545 x 599 x 338 mm 478 mm; CP5225dn: 718 x 702 x 478 mm	c space, USB or Ethernet port; (full install); Windows bit colour display, CD-ROM drive, Internet Explorer space; CD-ROM drive; USB or Ethernet port attion, Ready) /- 2 Hz), 6 A. Consumption: 440 watts (active), 30 % RH. Recommended operating humidity: 20 to			
Software Control panel Printer management Upgradability Power Dimensions (w x d x h) Weight	port; (full install); N port; (print driver o Vista®-64: 1 GHz 5.5 or higher, Mac Print driver (HP PCL 2-line, 16-character SNP (default install Memory upgradeal Requirements: Input watts (standby), 4.4 Out of package: CP5225 Out of package: 40 Packaged: CP5225 Out of package: 41 Packaged: 43 kg Operating tempera 60% RH . Storage Safety certifications GB4943-2001, Lov EMC certifications:	ticrosoft® Windows® XPx64: any Pentium® II pronly); Windows Vista®-32 Home, -32 Professional: processor, 512 MB RAM, 250 MB hard disk space. OS X v10.3 or higher; PowerPC G3, G4, G5, or .6), Toolbox FX configuration utility, SNP alerts and backlit front panel display, 5 buttons (Cancel job,), Toolbox FX (additional software install) ble to 448 MB, optional 500 sheet tray, only one of twoltage 115 to 127 VAC (+/- 10%), 60 Hz (+/- 14 watts (powersave), 0.5 watts (off); Typical Electric P5225: 545 x 599 x 338 mm; CP5225n: 545 x 50.9 kg. Thure: 10 to 30° C . Recommended operating temperature: 0 to 35° C. Storage humidity: 10 to 50 to 150 kg. The control of the	1 GHz processor, 512 MB RAM, 250 MB hard disle, USB port; (full install); SVGA 800 x 600 with 16-Intel® Core processor; 150 MB available hard disk distallation software on CD-ROM, Left arrow, Right arrow, Select, Back), 2 LEDs (Atteradditional tray may be added 2 Hz), 12 A; 220 to 240 VAC (+/- 10%), 50 Hz (+city Consumption (TEC): 1.787 kWh/Week 99 x 338 mm; CP5225dn: 545 x 599 x 338 mm 478 mm; CP5225dn: 718 x 702 x 478 mm	c space, USB or Ethernet port; (full install); Windows bit colour display, CD-ROM drive, Internet Explorer space; CD-ROM drive; USB or Ethernet port attion, Ready) /- 2 Hz), 6 A. Consumption: 440 watts (active), 30 /- 2 Hz), 6 A. Consumption: 440 watts (active), 30 /- 2 Hz), 6 A. Consumption: 440 watts (active), 30 /- 2 Hz), 6 A. Consumption: 440 watts (active), 30 /- 2 Hz), 6 A. Consumption: 440 watts (active), 30 /- 2 Hz), 6 A. Consumption: 440 watts (active), 30 /- 2 Hz), 6 A. Consumption: 440 watts (active), 30 /- 2 Hz), 6 A. Consumption: 440 watts (active), 30 /- 2 Hz), 6 A. Consumption: 440 watts (active), 30 /- 2 Hz), 6 A. Consumption: 440 watts (active), 30 /- 3 Hz), 6 A. Consumption: 440 watts (active), 30 /- 3 Hz), 6 A. Consumption: 440 watts (active), 30 /- 3 Hz), 6 A. Consumption: 440 watts (active), 30 /- 3 Hz), 6 A. Consumption: 440 watts (active), 30 /- 3 Hz), 6 A. Consumption: 440 watts (active), 30 /- 3 Hz), 6 A. Consumption: 440 watts (active), 30 /- 4 Hz), 6 A. Consumption: 440 watts (active), 30 /- 4 Hz), 6 A. Consumption: 440 watts (active), 30 /- 4 Hz), 6 A. Consumption: 440 watts (active), 30 /- 4 Hz), 6 A. Consumption: 440 watts (active), 30 /- 4 Hz), 6 A. Consumption: 440 watts (active), 30 /- 5 Hz), 6 A. Consumption: 440 watts (active), 30 /- 5 Hz), 7 Hz),			

http://www.hp.com/uk













